

ANSUNG

ANSUNG FRONT END LOADER

Ansung equipment produces more power, better performance and superior strength.

SPECIFICATIONS

| Ansung Model | BH680 | BK976 | BK996 | BK440 |
|--|------------------------------|------------------------------------|--------------------|--------------------|
| A. Digging Depth | 72.5" | 7'6" | 7'6" | 7'6" |
| B. Reach from center line of Swing Pivot | 96.3" | 9'4" | 9'4" | 9'4" |
| C. Loading Height (Bucket @ 60°) | 54.5" | 6'7" | 6'7" | 6'7" |
| D. Maximum Leveling Angle | 8° | 8° | 8° | 8° |
| E. Swing Arc | 150° | 180° | 180° | 180° |
| F. Transport Height (Maximum) | 5'0" | 6'3" | 6'3" | 6'3" |
| G. Transport Overhang | 4'1" | 4'1" | 4'1" | 4'1" |
| H. Bucket Rotation | 180° | 180° | 180° | 180° |
| J. Stabilizer Spread (Down Position) | 75" | 7'2" | 7'2" | 7'2" |
| L. Stabilizer Spread (Up Position) | 50" | 4'8" | 4'8" | 4'8" |
| M. Angle of Departure | 20° | 20° | 20° | 20° |
| N. Undercut | 32° | 3'0" | 3'0" | 3'0" |
| Bucket cylinder digging force | 2,200 lbs. | 3,080 lbs. | 3,080 lbs. | 3,080 lbs. |
| Dipper stick cylinder digging force | 1,180 lbs. | 2,160 lbs. | 2,160 lbs. | 2,160 lbs. |
| Shipping weight (Including Bucket) | 1,300 lbs. | 1,300 lbs. | 1,300 lbs. | 1,300 lbs. |
| Hydraulic pressure requirements | 1,780 psi. | 2,350 psi. | 2,350 psi. | 2,350 psi. |
| Recommended Tractor | B2320/B2620 B2920 | L3200/L3800 L2800/L3400 | L3240/L3540 | L4600/L4400 |



Ansung-USA, LLC.

1402 Dunn Dr. Suite 110 Carrollton TX 75006

Office : 972-242-4761 Cell : 469-877-5242 Fax : 972-242-3561


Email : sales@ansungusa.com

<http://www.ansungusa.com>



ANSUNG delivers a reliable efficient loader that enables you to achieve greater productivity.

ANSUNG



SPECIFICATIONS

| Ansung Loader Model | B2405 | B3605 | 2545C | 4705C | 2150B | 5070 | 8595 | 1950 | 2050 | 2150 |
|---|----------------------------|-------------------------|---------------------------------------|-------------------------------------|------------------|-------------------------|----------------------------|----------------|----------------|-------------------------|
| Tractor Model | BX2350 BX2360 BX2660 | B2320 B2620 B2920 | L3200/L3800 L2800/L3400 L3700SU | L4600/L4400 L3130/L3430 L3830 | MX5100 MX4700 | M5140 M6040 M7040 | M8560/M9560 M8540/M9540 | L3240 L3540 | L3940 | L4240 L5240 L5740 |
| A. Maximum Lift Height | 71.8" | 78.8" | 101.7" | 104.6" | 113.0" | 125.6" | 133.8" | 104.7" | 105.3" | 113.0" |
| B. Clearance w/Attachment Level | 66.1" | 73.1" | 95.5" | 100.6" | 101.5" | 101.7" | 121.3" | 98.0" | 98.8" | 101.5" |
| C. Clearance w/Attachment Dumped | 53.7" | 61.7" | 79.7" | 82.5" | 80.9" | 79.8" | 99.8" | 77.7" | 77.8" | 80.9" |
| D. Reach @ Maximum Height | 25.6" | 22.2" | 19.7" | 19.8" | 16.7" | 18.7" | 24.6" | 25.0" | 23.8" | 16.7" |
| E. Maximum Dump Angle | 45° | 40° | 42° | 48° | 60° | 74° | 57° | 52° | 53° | 60° |
| F. Reach w/Attachment on Ground | 48.5" | 49.2" | 59.8" | 65.6" | 79.1" | 74.4" | 78.7" | 71.0" | 74" | 79.1" |
| G. Attachment Rollback Angle | 25° | 25° | 25° | 26° | 42° | 40° | 43° | 26° | 24° | 42° |
| H. Digging Depth Below Grade | 2.9" | 2.5" | 4.4" | 5.0" | 5.8" | 5.6" | 7.7" | 3.5" | 4.6" | 5.8" |
| J. Overall Height in Carry Position | 36.4" | 36.8" | 45.7" | 48.2" | 59.2" | 58.2" | 64.1" | 50.3" | 53.5" | 59.2" |
| L. Depth of Attachment (to pivot pin) | 17.8" | 17.8" | 23.2" | 23.2" | 24.0" | 26.5" | 26.5" | 23.6" | 24.0" | 24.0" |
| M. Height of Attachment | 17.0" | 17.0" | 22.2" | 22.2" | 23.7" | 26" | 26" | 22.2" | 23.7" | 23.7" |
| N. Depth of Attachment (to pivot point) | 19.7" | 19.7" | 26.3" | 26.3" | 30.5" | 32.2" | 32.2" | 28.9" | 30.5" | 30.5" |
| Lift Capacity to Full Height @ Pivot Pin | 780 lbs | 995 lbs | 1,205 lbs | 1,830 lbs | 2,450 lbs | 2,640 lbs | 3,000 lbs | 1,446 lbs | 1,900 lbs | 2,500 lbs |
| Breakout Force @ Ground Level, Pivot Pin | 1,030 lbs | 1,590 lbs | 2,460 lbs | 2,950 lbs | 4,215 lbs | 4,310 lbs | 5,500 lbs | 2,860 lbs | 3,425 lbs | 4,215 lbs |
| Relief Valve Setting (Loader Control Valve) | 1,777 psi. hyd | 1,991 psi. hyd | 2,490 psi. hyd | 2,490 psi. hyd | 2,560 psi. hyd | 2,873 psi. hyd | 2,873 psi. hyd | 2,560 psi. hyd | 2,560 psi. hyd | 2,560 psi. hyd |
| Lift Cylinder | 1.57" x 14.1" | 1.77" x 13.1" | 1.97" x 17.9" | 2.36" x 17.9" | 2.36" x 20.3" | 2.36" x 20.2" | 2.76" x 21.2" | 1.97" x 27.1" | 2.16" x 20.0" | 2.36" x 20.3" |
| Bucket Cylinder | 1.57" x 15.1" | 1.77" x 15.0" | 1.97" x 20.7" | 1.97" x 17.9" | 2.36" x 17.9" | 2.36" x 18.5" | 2.76" x 18.1" | 1.97" x 16.7" | 2.16" x 18.5" | 2.36" x 17.9" |
| Bucket Size | 50" | 50" | 60"/66" | 72" | 72" | 72" | 84" | 66" | 72" | 72" |